

HERED®

Auto-level Crawler Scissor Lift

HC0607EA

GB/CE/ANSI Compliance

HIGHLIGHTS

- Compact structure, light weight, accessible elevators.
- Motor and crawler Drive, low noise, stronger passing ability.
- Neutral Steering, suitable for small space operation.
- Large capacity batteries, strong endurance.

FEATURES

Standard

Automatic Braking System	Emergency Stop	Flashing Beacons
Rolling-out Deck	Tilt Sensor	Emergency Descent System
Foldable Guardrails	Safety Arm	Hour Meter
Charging Protection	Horn	Motion Alarm
Proportional Control	Forklift Pocket	Fault Diagnostic System
Automatic Leveling System		

Optional

- Load Sensing System
- AC Power to the Platform
- Air Tube to the Platform



*Grand in Sound
Sharp in Heart
Viture in Action*

連嘗有限公司

LINK ATTEMPT LIMITED

香港新界上水金錢金坑路9號DD92 Lot 937
DD92 Lot 937, Kam Tsin, 9 Kam Hang Road,
Sheung Shui, N.T., H.K

Tel: (852) 2494 0788 Fax: (852) 2426 6509
www.linkattempt.com

HERED®

Auto-level Crawler Scissor Lift

HC0607EA

GB/CE/ANSI Compliance

連嘗有限公司

LINK ATTEMPT LIMITED

香港新界上水金錢坑路9號DD92 Lot 937
DD92 Lot937, Kam Tsin, 9 Kam Hang Road,
Sheung Shui, N.T., H.K
Tel: (852) 2494 0788 Fax: (852) 2426 6509
www.linkattempt.com

Model	HC0607EA
Measurements	
A-Max.Platform Height	5.9m
Max.Working Height	7.9m
B-Platform Length	1.63m
C-Platform Width	0.74m
D-Max. Horizontal Extension	0.9m
E-Overall Height(Rail Unfolded)	2.39m
Overall Height (Rail Folded)	2m
F-Overall Length(with Ladder)	2.02m
G-Overall Width	1.47m/1.3m
H-Ground Clearance	80mm
Platform Capacity	250kg
Extension Capacity	113kg
Platform Allowable Occupants	2
Drive Speed(Stowed)	2.4km/h
Turning Radius	Neutral Steering
Lift/Descent Time(Unloaded)	16/34s
Gradeability	40%
Max. Inclination(Front/Rear)	X (20°/-16°) Y (14°/-14°)
Max.Outrigger Leveling	/
Drive	Front Crawler
Crawler	250mmX72mmX60mm
Power	
Batteries	8X12V/160Ah
Charger	100-240VAC/35A
Weight	
Weight	1890kg

