

Specifications

MODELS		AWP™-25S	
MEASUREMENTS	US	Metric	
Working height*	30 ft 10 in	9.57 m	
Platform height	24 ft 10 in	7.57 m	
A Height - stowed (Standard)	6 ft 6 in	1.98 m	
stowed (RT/Narrow)	6 ft 7 in	2.01 m	
B tilted back** (Standard)	—	—	
C Length - stowed (Standard)	4 ft 3.5 in	1.31 m	
stowed (RT/Narrow)	5 ft 3 in	1.60 m	
D Length - tilted back**	—	—	
E Width (Standard)	2 ft 5 in	.74 m	
Width (RT)	2 ft 6 in	.76 m	
Width (Narrow)	1 ft 11 in	.58 m	
PRODUCTIVITY			
Lift capacity	350 lbs	159 kg	
ANSI/CSA:			
F G Outrigger footprint (l/w) (Standard)	5 ft 1 in/4 ft 5 in	1.55/1.35 m	
Outrigger footprint (l/w) (RT/Narrow)	5 ft 4 in/4 ft 2 in	1.63/1.27 m	
H Corner access*** (Standard)	1 ft 2 in	.36 m	
Corner access*** (RT/Narrow)	1 ft 1 in	.33 m	
I J Wall access front/side (Standard)	3 in/1 ft 1 in	.08/.33 m	
Wall access front/side (RT/Narrow)	6 in/1 ft	.15/.30 m	
CE/AUS/PB Indoor:			
F G Outrigger footprint (l/w) (Standard)	5 ft 9 in/5 ft 1 in	1.75/1.55 m	
Outrigger footprint (l/w) (RT/Narrow)	5 ft 11 in/4 ft 10 in	1.80/1.47 m	
H Corner access*** (Standard)	1 ft 7 in	.48 m	
Corner access*** (RT/Narrow)	1 ft 8 in	.51 m	
I J Wall access front/side (Standard)	7 in/1 ft 5 in	.18/.43 m	
Wall access front/side (RT/Narrow)	10 in/1 ft 5 in	.25/.43 m	
CE/AUS/PB Outdoor:			
F G Outrigger footprint (l/w) (Standard)	9 ft 9 in/9 ft 2 in	2.97/2.79 m	
Outrigger footprint (l/w) (RT/Narrow)	9 ft 4 in/9 ft 4 in	2.84/2.84 m	
H Corner access*** (Standard)	2 ft 6 in	.76 m	
Corner access*** (RT/Narrow)	4 ft 4 in	1.32 m	
I J Wall access front/side (Standard)	2 ft 5 in/3 ft 6 in	.74/1.07 m	
Wall access front/side (RT/Narrow)	2 ft 5 in/3 ft 8 in	.74/1.12 m	
Platform Dimensions: (l/w/h)			
Standard	27/26/44.75 in	.69/.66/1.14 m	
Gated standard	27/26/44.75 in	.69/.66/1.14 m	
Gated narrow	26/20/44.75 in	.66/.51/1.14 m	
Standard fiberglass	29/26.5/43.5 in	.74/.67/1.10 m	
POWER			
Power source - AC or DC models	12V DC / 110/50-60 Hz or 220/50-60 Hz AC		
WEIGHT			
AC models (Standard)	727 lbs	330 kg	
AC models (RT/Narrow)	694 lbs	315 kg	
DC models (Standard)	817 lbs	371 kg	
DC models (RT/Narrow)	780 lbs	354 kg	
Air motor (Standard)	—	—	
Air motor (RT/Narrow)	—	—	
STANDARDS COMPLIANCE		ANSI A92.3, CSA B354.1, EN 280, AS 1418.10	