

AERIAL WORK PLATFORMS
AWP™ Super Series™



Specifications

MODELS		AWP™-30S	
MEASUREMENTS		US	Metric
Working height*		35 ft 6 in	11.00 m
Platform height		29 ft 6 in	9.00 m
A Height - stowed (Standard)		6 ft 6 in	1.98 m
stowed (RT/Narrow)		6 ft 7 in	2.01 m
B tilted back** (Standard)		—	—
C Length - stowed (Standard)		4 ft 5 in	1.35 m
stowed (RT/Narrow)		5 ft 3 in	1.60 m
D Length - tilted back**		—	—
E Width (Standard)		2 ft 5 in	.74 m
Width (RT)		2 ft 6 in	.76 m
Width (Narrow)		1 ft 11 in	.58 m
PRODUCTIVITY			
Lift capacity		350 lbs	159 kg
ANSI/CSA:			
F G Outrigger footprint (l/w) (Standard)		5 ft 9 in/5 ft 1 in	1.75/1.55 m
Outrigger footprint (l/w) (RT/Narrow)		6 ft/5 ft	1.83/1.52 m
H Corner access*** (Standard)		1 ft 7 in	.48 m
Corner access*** (RT/Narrow)		1 ft 7 in	.48 m
I J Wall access front/side (Standard)		5 in/1 ft 5 in	.13/.43 m
Wall access front/side (RT/Narrow)		7 in/1 ft 5 in	.18/.43 m
CE/AUS/PB Indoor:			
F G Outrigger footprint (l/w) (Standard)		6 ft 4 in/5 ft 8 in	1.93/1.73 m
Outrigger footprint (l/w) (RT/Narrow)		6 ft 11 in/6 ft 2 in	2.11/1.88 m
H Corner access*** (Standard)		1 ft 10 in	.56 m
Corner access*** (RT/Narrow)		2 ft 3.5 in	.70 m
I J Wall access front/side (Standard)		8 in/1 ft 9 in	.20/.53 m
Wall access front/side (RT/Narrow)		9 in/1 ft 8 in	.23/.51 m
CE/AUS/PB Outdoor:			
F G Outrigger footprint (l/w) (Standard)		9 ft 9 in/9 ft 2 in	2.97/2.79 m
Outrigger footprint (l/w) (RT/Narrow)		10 ft 10 in/11 ft 4 in	3.30/3.45 m
H Corner access*** (Standard)		2 ft 3 in	.69 m
Corner access*** (RT/Narrow)		5 ft 1 in	1.55 m
I J Wall access front/side (Standard)		2 ft 3 in/3 ft 6 in	.69/1.07 m
Wall access front/side (RT/Narrow)		2 ft 11 in/4 ft 7 in	.89/1.40 m
Platform Dimensions: (l/w/h)			
Standard		27/26/44.75 in	.69/.66/1.14 m
Gated standard		27/26/44.75 in	.69/.66/1.14 m
Gated narrow		26/20/44.75 in	.66/.51/1.14 m
Standard fiberglass		29/26.5/43.5 in	.74/.67/1.10 m
POWER			
Power source - AC or DC models		12V DC / 110/50-60 Hz or 220/50-60 Hz AC	
WEIGHT			
AC models (Standard)		777 lbs	352 kg
AC models (RT/Narrow)		729 lbs	331 kg
DC models (Standard)		867 lbs	393 kg
DC models (RT/Narrow)		818 lbs	371 kg
Air motor (Standard)		777 lbs	352 kg
Air motor (RT/Narrow)		729 lbs	331 kg
STANDARDS COMPLIANCE		ANSI A92.3, CSA B354.1, EN 280, AS 1418.10	

www.genieindustries.com